

P3305 Series Key Specifications		
Model	P3305DN	P3305DW
Specifications		
Print Speed	33ppm(A4) 35ppm(Letter)	33ppm(A4) 35ppm(Letter)
First Print out time	≤8.2s	≤8.2s
Monthly duty cycle	80000 Pages	80000 Pages
Recommended monthly page volume	1000 to 10000 pages	1000 to 10000 pages
Print resolution	Max.1200x600 dpi	Max.1200x600 dpi
Printer language	PCL5e、PCL6、PS3、PDF	PCL5e、PCL6、PS3、PDF
Processor speed	350MHz	350MHz
Memory	256MB	256MB
Control panel	2Line LCD	2Line LCD
Duplex model	Automatic	Automatic
NFC	No	Yes
Paper handling		
Paper input tray	250Pages	250Pages
Multipurpose tray	1 Pages	1 Pages
Paper output tray	120Pages	120Pages
Media types	Plain, Thick, Transparency, Cardstock, Lable	Plain, Thick, Transparency, Cardstock, Lable
Media sizes	A4, A5, JIS B5, ISO B5 , A6, Letter, Legal,Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6 , Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	A4, A5, JIS B5, ISO B5 , A6, Letter, Legal,Executive, Folio, Oficio, Statement, Japanese Postcard, ZL, Big 16K, Big 32K, 16K, 32K, B6 , Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media weight	input tray : 60-105g/m ² Multipurpose tray : 60-200g/m ²	input tray : 60-105g/m ² Multipurpose tray : 60-200g/m ²
Other		
Dimensions (w*d*h)	354 x334x 232mm	354 x334x 232mm
Wight (without toner cartridge)	6.8kg	6.8kg
Operating temperature range	10 ~ 32℃	10 ~ 32℃
Operating humidity range	20% ~ 80% RH	20% ~ 80% RH
Input voltage	AC100-127V, 50/60Hz(±2Hz) , 9A AC220-240V, 50/60Hz , 4.5A	AC100-127V, 50/60Hz(±2Hz) , 9A AC220-240V, 50/60Hz , 4.5A
Noise	Printing : ≤52dBA Standby : ≤30dBA	Printing : ≤52dBA Standby : ≤30dBA
Power consumption	Print: Average 525W Standby: 50W Dormant : Less than 2 W	Print: Average 525W Standby: 50W Dormant : Less than 2 W
Operating system compatibility	Windows Server2003/2008/2012/ XP/Vista/Win 7/Win 8/Win8.1/ Win10 (32/64 bit) Mac OS 10.7 ~ 10.13 Linux : Ubuntu 12.04/14.04/16.04/18.04 (32/64 bit)	Windows Server2003/2008/2012/ XP/Vista/Win 7/Win 8/Win8.1/ Win10 (32/64 bit) Mac OS 10.7 ~ 10.13 Linux : Ubuntu 12.04/14.04/16.04/18.04 (32/64 bit)
Interface	High-speed USB 2.0 Ethernet : IEEE 802.3 10/100Base-Tx	High-speed USB 2.0 Ethernet : IEEE 802.3 10/100Base-Tx WiFi : IEEE 802.11b/g/n
Supplies		
Cartridge style	Toner Cartridge & Drum Unit	Toner Cartridge & Drum Unit
Starter toner capacity (1)	TL-425H (3000 Pages)	TL-425H (3000 Pages)
Starter drum unit lifetime(2)	DL-425X (25000 Pages)	DL-425X (25000 Pages)
Standard toner capacity (1)	TL-425H (3000 Pages) TL-425X (6000 Pages) TL-425U (11000 Pages)	TL-425H (3000 Pages) TL-425X (6000 Pages) TL-425U (11000 Pages)
Standard drum unit lifetime (2)	DL-425X (25000 Pages)	DL-425X (25000 Pages)

Note: (1) Toner capacity is based on ISO 19752.

(2) Drum unit lifetime is based on 3 average letter/A4-size pages per print job and 5% coverage,actual lifetime affected by different printing habits and printir

ig environment.